



# 承认书

## SPECIFICATION FOR APPROVAL

客户 Customer	:	
客户批号 Customer Part No.	:	
并日型号 Bingri Part No.	:	S3535P29L0Y002
制作人 Prepared By	:	日期 Time: 2019/09/8
审核 Checkedy	:	日期 Time: 2019/09/08
客户回签 Customer Comfirmation	:	日期 Time:

并日电子科技（深圳）有限公司

BING RI ELECTRONIC TECHNOLOGY (S.Z.) CO.,LTD

3-4F,B3 Merchants Guangming Science Park , Guangung Road, Guangming New District, Shenzhen

Tel: +86-755-27166966 27166662 27166663

Fax: +86-755-27166691

客户意见栏 ( Customer' S Proposal)

Approve 承认 (请于认可栏中签名)       Disagree 不同意

Reason 原因: \_\_\_\_\_

版本 ( Version): 1.3




● **Features:**

1. Emitted Color: UVC
2. Lens Appearance: Clean quartz lens
3. 3.5x3.5x1.6mm standard package.
4. Suitable for all SMT assembly methods.
5. Compatible with infrared and vapor phase reflow solder process.
6. Compatible with automatic placement equipment.
7. This product doesn't contain restriction Substance, comply ROHS standard.

● **Applications:**

1. Sterilize

● **Package Dimensions:**



NOTES:

1. All dimensions are in millimeters.
2. Tolerance is  $\pm 0.10$ mm unless otherwise specified.
3. Specifications are subject to change without notice.

● **Part Numbering System:**

<u>S</u>	<u>3535</u>	<u>P2</u>	<u>9L</u>	<u>0</u>	<u>Y</u>	<u>002</u>
(1)	(2)	(3)	(4)	(5)	(6)	(7)

- (1) B: Substrate code
- (2) Package type: 3535
- (3) LED Color: P2 means UVC segment
- (4) Chip code
- (5) 0: CRI not required
- (6) Y: Type of adhesives
- (7) 002: Specification difference code



**ATTENTION**  
OBSERVE PRECAUTIONS  
FOR HANDLING  
ELECTROSTATIC  
DISCHARGE  
SENSITIVE  
DEVICES



● **Absolute Maximum Ratings (Ta=25°C)**

Item	Symbol	Value	Unit
Power Dissipation	PD	0.4	W
DC Forward Current	IF	50	mA
Single Chip Pulsed Forward Current	IFP	50※	mA
Reverse Voltage	VR	5	V
Operating Temperature	Topr	-30 ~ +80■	°C
Storage Temperature	Tstg	-40 ~ +120	°C
Soldering Temperature	Tsol	260for5sec△	°C

※Duty 1/10, Pulse Width 0.1ms.

△Soldering time max 10sec

■please refer to IF-Ta diagram of curves for the temperature during application

● **UVC parameter**

50mA

Parameter	Symbol	Value			Unit	Test condition
		Min.	Typ.	Max		
Forward Voltage	Vf	5.5	6.5	7.5	V	If=50mA
Reverse Current	Ir	-	-	10	μ A	Vr=5V
Viewing angle	2θ1/2	-	120	-	Deg	If=50mA
Peak Wavelength	λp	270	275	280	nm	If=50mA
Luminous Power	Po	5	6	8	mw	If=50mA



● **Soldering :**

1. Manual Soldering


The temperature of the iron tip should not be higher than 350°C and Soldering time to be within 3 seconds per solder-pad.

2. Reflow Soldering

Preheating : 140°C~160°C±5°C, within 2 minutes.

Operation heating : 260°C (Max.) within 10 seconds. (Max)

Gradual Cooling (Avoid quenching).



● **Storage:**

In order to avoid the absorption of moisture, it is recommended to solder BINGRI LEDs as soon as possible after unpacking the sealed envelope.

If the envelope is still packed, to store it in the environment as following:

- (1) Temperature : 5°C-30°C (41°F) Humidity : RH 60 % Max.
- (2) After this bag is opened, devices that will be applied to infrared reflow, vapor-phase reflow, or equivalent soldering process must be:
  - a. Completed within 168 hours.
  - b. Stored at less than 30% RH.
- (3) Devices require baking before mounting, if:
  - (2) a or (2) b is not met.
- (4) If baking is required, devices must be baked under below conditions:  
48 hours at 60°C±3°C.